

TRANSNET NATIONAL PORTS AUTHORITY**SUPPLY, DELIVERY AND OFF-LOADING OF PAINT MATERIALS AND PAINT CONSUMABLES IN THE PORT OF DURBAN ON AN "AS AND WHEN REQUIRED" BASIS FOR A PERIOD OF THIRTY-SIX (36) MONTHS****1. DESCRIPTION**

The purpose of this contract is for the supply, delivery and off-loading of paint materials and paint consumables in the Port of Durban on an "as and when required" basis for a period of thirty-six (36) months.

2. DURATION OF CONTRACT

The contract period will be thirty-six (36) months from the date of the contractor being notified of the acceptance of his tender till the end of the thirty-six (36) months **or the monetary value whichever comes first**. No guarantee of any quantities can be given, the Supplier will be required to supply the items under this contract, on "an as and when required" basis and in such quantities as may be required during the period of this contract.

3. SPECIFICATIONS**3.1 DELIVERY**

Company signage must always be displayed, on the vehicles entering the Port of Durban.

All material to be delivered to the following locations as and when required in the Port of Durban: 11 Methven Road, 223 Maydon Road, Kings Rest, Berth 100 (Divers Workshop), Island View (Roads & Track depot) and Fynnland (PSS Depot).

The supplier will be responsible for the offloading of all materials.

All vehicles delivering materials to the Port are to be Roadworthy condition and the Supplier may not carry employees at the back off the vehicles.

All material to be delivered during working hours Monday-Friday are 07:00am – 15:30pm

The Supplier will be responsible for all spillages and damages to any materials during offloading and must ensure that the affected areas are cleaned up and replaced if needed.

Pricing to include pick up, delivery and offloading charges.

3.2 PACKING

The supplier shall provide such packing of the goods as is required to prevent their damage or deterioration during transit to their destination, as indicated in the contract. The packing shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage.

3.3 DELAYS

The Supplier will be expected to effectively deliver the required items within the agreed time from receiving an official order from Transnet National Port Authority and failing to do so, the Supplier will be required to pay Transnet National Port Authority a penalty charge equal to 10% of the Purchase order value.

Should the Supplier have reason to suspect delays in delivery, the Supplier shall advise the Purchaser upon receipt of an order in writing of any anticipated delays citing reasons therefore and put forward a new anticipated delivery. The Purchaser may then extend the delivery date if the reasons given are justified and proof submitted that the delays are out of the Supplier control.

TRANSNET NATIONAL PORTS AUTHORITY**3.4 QUALITY**

All materials and supplied for Transnet must comply with the relevant SABS (South African Bureau of Standards), SANS (South African National Standards) and ISO (International Organization for Standardization)

All Goods supplied shall comply with the requirements of the Scope of Work or shall conform in all respects to which form part of the Contract. All paint to come with a manufacturing Guarantee. The Supplier shall also guarantee that, at the time of delivery, the commodity supplied under the contract will be new and free from any defects in material. It must also conform to the requirements of the contract. In case that any defects or non-conformity of the contract occurs, the Supplier must resolve the problem within 7 days. The Supplier shall furnish without extra charge all material data sheets, SABS, SANS documentation etc.

3.5 MATERIAL SPECIFICATIONS

Where no description is given for an item, it still must comply with the relevant SABS and SANS standard. Materials shall be new, unused, best of their respective kinds and free from defects.

If the Supplier fails to supply Goods, materials or services in accordance with the provisions of the Contract, the Transnet may reject any part of the Goods by giving written notice to the Supplier specifying the reason for rejection and whether replacement Goods are required and within what time. All rejects shall be held at the Supplier's risk and expense including all transportation and handling costs until returned to or collected by the Supplier. All rejects shall be replaced or rectified and made good at the Supplier's expense within the specified time.

All materials are to bear the mark of the South African Bureau of Standards where a standard is applicable to the material.

- **Red Oxide Metal primer**

Red oxide primer must have anti-corrosion coating designed to stop rust formation. Must be able to apply directly over a rusty surface. Should be quick drying solvent-based primer. Packaging should be in 5 litre containers which must be clearly marked.

- **Wood Varnish**

The product should be suitable for many different applications such as wooden floors, doors wooden frames, etc. Packaging should be in 5 litre containers which must be clearly marked

- **High gloss paint**

Must be suitable for the protection and decoration exterior metal surfaces where a glossy durable finish is required. Should have a high gloss appearance. Packaging should be in 5 litre containers which must be clearly marked.

- **Thinners SABS approved**

The product should be used for many different applications such as, cleaning paint brushes and rollers, removing dirt, oils and any other. Thinners to be Grade A. Packaging should be in 5 litre containers which must be clearly marked.

- **Mineral Turpentine**

The product should be used for many different applications such as, hydrocarbon solvent for cleaning paint brushes and rollers, removing dirt, oils and any other. Turpentine should be slow evaporating and appearance should be water like liquid. Packaging should be in 5 litre containers which must be clearly marked.

TRANSNET NATIONAL PORTS AUTHORITY

- **Polyurethane enamel paint non-Drip**
Product should be a Non-Drip Enamel polyurethane eggshell for interior and exterior use, should also be resistant to water and steam and scratch. Must compile SANS 630 for Decorative Polyurethane enamel paint. Packaging should be in 5 litre containers which must be clearly marked.
- **Epoxy Floor Paint with harder and non-slip Grip Additive**
The product should be suitable for workshop floor and shower floors. The floor coating which must contains non-slip grip additive particles, must be extremely tough and non-slip, even in wet conditions, specially designed for exterior and interior use. Must have excellent gloss retention, durability and chemical resistance.
- **Solvent free epoxy**
Must be suitable for tank coating for drinking water, excellent long-term corrosion prevention in extremely corrosive environments in the Port. Epoxy must include curing agent. Packaging should be in 5 litre containers which must be clearly marked.
- **Road Paint marking SABS approved**
The paint required must be of quick drying kind for the use of bituminous and concrete surfaces. The paint must be suitable for brush and roller application. The paint must comply in all aspects to the latest addition of the SABS standard specification 731/Road marking. The colours required will be white, yellow, red and black. Packaging of Road marking paint to be in 20L Steel Containers for White, Yellow, Red, and Black Paint.
- **Cold galvanize spray**
Should be suitable for repairing defects on galvanized items and applied as a stand-alone coating on galvanized steel. Cold Galvanizing spray Aerosol to come in a 400ml tin.
- **Cold galvanizing paint**
Should be suitable for repairing defects on galvanized items and applied as a stand-alone coating on galvanized steel with maximum corrosion protection. Packaging should be in 5 litre containers which must be clearly marked.
- **Universal undercoat**
A top-quality alkyd-based undercoat for all interior and exterior primed metal, wood, plaster and various types of Composition board. Must be a suitable undercoat for High Gloss Enamel, and Eggshell Enamel. Packaging should be in 5 litre containers which must be clearly marked.
- **White PVA (Polyvinyl Alcohol) paint**
Super Acrylic PVA, Surface Appearance Matt, must be of Low odour. Suitable for exterior and interior walls and ceilings. Packaging should be in 5 litre containers which must be clearly marked.
- **Damp seal SABS approved**
Must be suitable for both interior and exterior use. Must effectively seal the surface, protect against penetrating dampness and peeling paint. Packaging should be in 5 litre containers which must be clearly marked.

TRANSNET NATIONAL PORTS AUTHORITY

- **Stoep Enamel**
Must be suitable for concrete, cement floors windowsills, etc. Should have a gloss appearance that can be polished. Packaging should be in 5 litre containers & clearly marked.
- **Interior Paint**
Must be suitably new and old interior cement plaster walls, fibreboards, ceiling boards, gypsum, plaster, metal and wood. Interior use only with multi-layered protective coating preventing dirt from penetrating the paint. Should be low odour premium quality velvet sheen wall coating that is highly washable and stain resistant. Packaging should be in 5 litre containers which must be clearly marked.
- **Exterior Paint**
Must be suitable for all weather and marine environment. Water- weather and UV-resistant Endure All-Weather Matt is water-, weather- and UV-resistant. The paint must washable, smooth finish, water-based, low splatter, low odour and quick drying. Packaging should be in 5 litre containers which must be clearly marked.
- **Brick Seal**
Must be suitable to use as a water repellency on unpainted bricks, stones, concrete and other masonry materials. Should protect joints from decay caused by acidic atmosphere. Packaging should be in 5 litre containers which must be clearly marked.
- **Bituminous Aluminium Paint**
Bituminous based aluminium paint which must be suitable for concrete and metal roofs. It should also improve illumination and reflects heat. Resistant to humidity, salt water and exterior exposure conditions. Packaging should be in 5 litre containers which must be clearly marked.
- **Pure Acrylic Waterproof Paint**
A premium pure acrylic waterproofing paint used in conjunction with membrane, to form a tough, flexible waterproofing barrier to seal joints and cover fine cracks on roofs and walls. Packaging should be in 5 litre containers which must be clearly marked.
- **Anti Corrosive Paint**
A two component, high gloss, polyurethane finish. Capable of drying to low temperatures. Can be applied by spray, brush and roller.
This paint comes in 2 parts: PART A has a quantity of 4 litre and PART B has a quantity of 2.86 litre, but both must be supplied in 5 litre containers. It is used for coating of steel surfaces in a coastal environment, eg. Power transformers, steel light poles, steel structures, etc. Colour required are white and grey
- **Road Marking Glass Beads**
Hardness: 6-7 Moh scale
Specific weight: $\pm 2.5 \text{ g/cm}^3$
Bulk density: $\pm 1.6 \text{ kg/L}$
Free silica: None
Shape: round
Reflectivity Nd: 1.5 for coated and uncoated
Storage Dry, sheltered storage conditions
Sieving Range
150 – 850 SP

TRANSNET NATIONAL PORTS AUTHORITY

Size range in microns

>850 – 0%

600–850 – 17.4%

300-600 – 59%

180-300 – 21.5%

<180 – 2.1%

- **Paint brush**
Must be of superior quality synthetic bristle encased in a stainless-steel ferrule, Rust-resistant, stainless-steel ferrule. High volume bristle content for multiple paint applications with smooth, even finish with all coatings. Extra thick bristle content for maximum paint pick up and even release.
- **Paint Roller Mohair**
High quality, natural wool blend, short pile resulting in less paint spatter on smooth surfaces
Should be virtually lint free and Thermo-bonded core with roller fabric heat-fused to the core, ensuring high resistance to solvents and no unwinding.
- **Scraper**
Suitable for removal of old paint, rust & glue.
- **Duct tape**
Waterproof tape suitable for fixing, protecting, and packaging and sealing.
- **Polyfilla Exterior Crack Filler**
Must be suitable for repairs to all masonry, concrete, stone, plaster, or other exterior.
- **Polyfilla Interior Crack Filler**
Must be suitable for repairs on all interior cement and gypsum, plaster, wood and other masonry surfaces before painting.
- **Sugar Soap**
For removal of wax, grease and grime from walls prior to painting Ensures a clean and ready-to-paint surface.
- **Extension Pole**
Should be suitable when painting high areas to extend roller handle.
- **Deep Roller Tray**
Must be suitable for all paint types, for exterior and interior use. Must be easy to use and easy to clean.
- **Sandpaper Roll**
Should be suitable for general purpose use, ideal for sanding off old paint.